CALFED WATER QUALITY

PRELIMINARY LOADING ANALYSIS

CONTENTS

- 1) CONSTITUENT SELECTION TABLE
- 2) SOURCE SELECTION TABLE
- 3) COPPER (80% Complete)
- 4) MERCURY (40% Complete)
- 5) SELENIUM (90% Complete)
- 6) CHLORPYRIFOS (40% Complete)
- 7) DIAZINON (60% Complete)
- 8) CARBOFURAN (40% Complete)
- 9) NITRATE (40% Complete)
- 10) REFERENCES
- 11) INTERNET SEARCH

Prepared for



CALFED Water Quality Action Team Sacramento, CA

April 18, 1997

PRELIMINARY LOADING ANALYSIS

INTRODUCTION AND PURPOSE

The purpose of the analysis is to estimate the loads of various pollutants discharged to water bodies within different portions of the CALFED study area. The pollutants of interest are the key contaminants identified by the CALFED advisory committees. Load estimates were made for four regions, the Sacramento River Basin, the San Joaquin River Basin, the Delta, and the Bay Region. The Sacramento River Basin estimates were further subdivided into loads generated above and below the three major dams, Shasta, Oroville and Nimbus.

In a later task in the CALFED program, the load estimates will be used to determine the relative importance of different pollutant sources and the effectiveness of potential control measures. For example, it may be determined that municipal and industrial wastewater treatment plants contribute less than 5% of the copper discharges to the Delta. It is apparent from the loading estimate described above for copper that additional measures to reduce copper from this source are unlikely to greatly affect copper concentrations in the Delta.

ANALYTICAL APPROACH AND ORGANIZATION OF INFORMATION

Considerable information on pollutants discharged to the Sacramento River Basin, the San Joaquin River Basin, the Delta, and the Bay Region and pollutant concentrations in various water bodies is available but it is not found in a single depository. Developing a comprehensive picture of pollutant loadings involves compilation of potentially-relevant data from published and unpublished sources, review of the data by the consultant team and, in many cases, further manipulation of the data into the form of load estimates.

Pollutant load estimates are difficult to make for large geographical areas because data is always limited and many assumptions have to be made. The approach used here was to try to make fairly complete load estimates for the various contaminants even if fairly gross assumptions have to be made. The load estimates will then be progressively refined as additional data is acquired and analyses completed.

The following analytical report includes a number of separate sections addressing each key contaminant. Each section consists of a tabular and graphical summary of loading data and a series of notes. The notes describe the data sources and any analyses undertaken by the consultant team to produce the load estimates.

Two approaches to load estimation were used and their results compared in the tabular and graphical summaries. The first approach was to estimate the load attributable to each major source and then to sum the loads up to provide a total basin load. Major contaminant source

X:\CALFED\INTRO.DOC

ii

categories include agricultural stormwater runoff and subsurface drainage, mine drainage, municipal and industrial wastewater discharges and urban stormwater runoff. The second approach was to estimate the total pollutant emission from a basin by calculating the load contained in water exiting the basin at its downstream end. The loads calculated using the two approaches are not directly comparable because some of the pollutants discharged to waterways in a basin may be stored in sediments and biota or transformed into other substances, as a consequence of chemical reactions and biological activity.

LIMITATIONS

Because of the many assumptions and simplifications involved in the load estimates the results need to be used with caution. The more important assumptions and simplifications are noted below.

Year-to-year variations

Most contaminant sources are affected by meteorological conditions. The total contaminant loads from agricultural and urban runoff depend on the volume of runoff which can vary widely from year-to-year. Mine drainage loads are similarly weather-dependent. Waste loads associated with municipal and industrial wastewater discharges are less affected by weather; the same may be true for waste loads in agricultural subsurface drainage which probably depend more on irrigation rates than precipitation.

Because the data available to characterize contaminant loads is limited it was not separately compiled for different meteorological conditions. Ideally, loads should be separately estimated for wet, normal, dry and very dry years. Instead data from different years, representing different meteorological conditions were compiled to produce a single load estimate that may approximate "typical" conditions.

Seasonality of loadings

Most contaminant emissions vary seasonally. The initial load estimates contained in this report were made on an annual basis. If the available data allows, later refinement of the load estimates will seek to account for seasonality.

Background loads

The load estimates do not attempt to account for background loads. Many substances regarded as contaminants occur at low concentrations in waters uninfluenced by human activities. This is the case for metals and trace elements, salts, naturally-occurring organic substances and plant nutrients. It is not so for synthetic organic including pesticides.

X:\CALFED\INTRO.DOC

iii


The lack of allowance for background loads probably does not greatly affect load estimates for relatively concentrated waste streams. If, for example, a city draws water from a river, uses it for municipal supply and discharges it back to the river after wastewater treatment then the phosphorus load attributable to the municipal wastewater discharge is the load contained in the effluent less the background load contained in the source water. In this case, the background phosphorus concentration might be 0.05 mg/l while the concentration of phosphorus in the wastewater effluent would be 5 or 10 mg/l. The phosphorus load would be similar whether or not the background concentration is allowed for.

Lack of an adjustment for background loads can have a greater effect on loads attributable to dilute, but high-volume, waste streams. For example, copper concentrations in agricultural runoff may be estimated to be 0.01 mg/l while copper concentrations in runoff from non-agricultural lands with similar soil chemistry characteristics may be 0.005 mg/l. Not accounting for the background concentration in the load calculations would result in an overestimation of loads attributable to agricultural runoff by a factor of 2.

iv

				CONSTI	FUENT SE	LECTION TABL					
						Ecological/Hum	nan Health				
		5	30	3(d) List							
Туре	Constituent	Delta	Sacramento Basin	San Joaquin Basin	Bay Region	Sacramento R. (above dams)	Drinking Water	Agricultural Water	Industrial	Recreational	LOADING LIST
Metals	As						 				
	Cd										
	Cr			•			7				
	Cu						Ī				
	Hg										
	Pb						7				
	Ni						. 1				L
	Zn										5.40
Trace El.	selenium boron										
Organics	TOC										
-	DOC										
	THM										
	THMFP						1				
	TFPC										
Pesticides	DDT		i								
	carbofuran		. 1931				1				- 4.6
	chlordane (A)		ومراوي والمهرون ويعيبوا								v. reina
	chlorpyrifos										
	diazinon	22.50	en et trock in it	C 1 18							· 李敬
	toxaphene (A)										- 1
	PCBs										100
	endosulfan (A)										
Salts	TDS		-								1
	salinity SAR										343
	bromide										~ (40)
	chloride										* 50 miles
Biotic	pathogens										7.85
Nutrients	nitrate		f				i.				
1471161112	phosphorous			i			T				
	ammonia			اندرسون							
Other	DO			S			+				
	turbidity										
	temperature			'							
	unk. toxicity						1				
	pH						1				
	alkalinity				•		7				, ,
	sediment.			ľ		-	1 '				


ì



				COPF	PER LOADING	TABLE	E			
		ı	Copp	er Load	ing (thousands of	pounds.	/year)	1	1	
Source	Delta	Note	Lower Sacramento Basin below dams	Note	San Joaquin Basin	Note	Bay Region	Note	Upper Sacramento Basin above Dams	Note
Agricultural	В	1	41	6	В	11	as Good Colored	16	¢yin n aa a	
Mine Drainage	4	2	274	7	4	12	Signatura di Garanti di	17	24°	
M&I Wastewater (POTW)	2	3	9	8	A	13	55	18		
Urban Runoff	6	4	24	9	9	14	73	19	i i	
Flow Regulation										
Total Load			348		13		128			
Basin Emission	A	5	В	10	Α	15	,	20	56	21

Note: Numerical values listed in italics under the Note column provide the background and references associated with the accompanying load A - Data available; flow and concentration data available; load calculations required.

⁻ Source does not contribute significant load of constituent in this watershed.



B - Further literature review required.

Copper Loading Notes

- 1. Further literature review required.
- 2. The original data for the load estimate was obtained from "A mass loading assessment of major point and non-point sources discharging to surface waters in the Central Valley, California, 1985" prepared by the RWQCB Central Valley Region in 1988. Flow and load data was compiled for four inactive mines including Iron Mountain, Newton, New Idria and Afterthought Mines. Only mines that drain to the Sacramento River or its tributaries below Shasta, Oroville and Nimbus Dams were considered. Ninety-five percent of the load was from Iron Mountain. A later report by Central Valley RWQCB prepared in 1989 and entitled "A mass loading assessment of major point and non-point sources in the Sacramento Valley, California, 1985" estimated that the earlier mine drainage estimate only represented 25% of the total. A further review of the two RWQCB documents was made by Woodward-Clyde in light of information contained in a 1992 report by the Central Valley Board entitled "Inactive mine drainage in the Sacramento Valley". Data in this report suggests that Iron Mountain represents about 50% of the total copper load from inactive mines. The 50% estimate was used to scale up the loads originally calculated by RWQCB. The loads calculated in the 1988 RWQCB were segregated into the three geographical areas, delta, San Joaquin Basin and Sacramento Basin below dams.
- 3. The original data for the load estimate was obtained from "A mass loading assessment of major point and non-point sources discharging to surface waters in the Central Valley, California, 1985" prepared by the RWQCB Central Valley Region in 1988. Flow and load data was compiled from several NPDES dischargers who have been monitoring copper. including the largest in the Central Valley the Sacramento Regional County Sewer District. Woodward-Clyde divided the results into two geographical areas, the delta and the Sacramento Basin. A later report by Central Valley RWQCB prepared in 1989 and entitled "A mass loading assessment of major point and non-point sources in the Sacramento Valley, California, 1985" estimated that the earlier M and I estimate only represented 50% of the total. This percentage was used to scale up the loads.
- 4. The original data for the load estimate was obtained from "A mass loading assessment of major point and non-point sources discharging to surface waters in the Central Valley, California, 1985" prepared by the RWQCB Central Valley Region in 1988. Urban runoff estimates were made for 19 large cities in the Central Valley. Flow data was calculated using rainfall data for cities, urban acreage and a runoff factor of 0.3. Quality data for the city of Sacramento was used for all cities. A later report by Central Valley RWQCB prepared in 1989 and entitled "A mass loading assessment of major point and non-point sources in the Sacramento Valley, California, 1985" estimated that the earlier urban runoff estimate only represented 35% of the total. A further review of the original data by Woodward-Clyde concluded that the original estimate probably captured 70% of the load, because all major urban areas were included in the calculations. The 70% figure was used to scale up the original estimates. The data allowed separation of the loads into three geographical areas, the delta, San Joaquin Basin and the Sacramento Basin.
- 5. Copper concentrations are available from various sampling locations within the Delta and at the San Joaquin River inflow to the Delta. Most of this data can be found at the Interagency

Copper Loading Notes

Ecological Program web site. Work is in progress to acquire matching discharge data and calculate loads.

- 6. The original data for the load estimate was obtained from "A mass loading assessment of major point and non-point sources discharging to surface waters in the Central Valley, California, 1985" prepared by the RWQCB Central Valley Region in 1988. Flow and concentration information was compiled for the major drains in the Sacramento Basin, including Sacramento Slough, Colusa Basin Drain, RD1000, RD108 and Natomas East Main Drain. A later report by Central Valley RWQCB prepared in 1989 and entitled "A mass loading assessment of major point and non-point sources in the Sacramento Valley, California, 1985" estimated that the earlier agricultural runoff estimate only represented 80% of the total. This percentage was used to scale up the estimates.
- 7. See Note 2 for explanation.
- 8. See Note 3 for explanation.
- 9. See Note 4 for explanation.
- 10. See Note 1 for explanation.
- 11. See Note 1 for explanation.
- 12. See Note 2 for explanation.
- 13. Data available; flow and concentration data available; load calculations required.
- 14. See Note 4 for explanation.
- 15. See Note 5 for explanation.
- 16. Source does not contribute significant load of constituent in this watershed.
- 17. See Note 16 for explanation.
- 18. Reported in Table 19 of "State of the Estuary: A report on conditions and problems in San Francisco Bay/Sacramento-San Joaquin Delta Estuary' San Francisco Estuary Project, 1992. Middle of range of values used .
- 19. See Note 18.
- 20. See Note 16 for explanation.
- 21. Total emission from upper Sacramento Basin was calculated using flow and concentration data for releases from Shasta, Oroville and Nimbus Dams. Reported in "A mass loading assessment of major point and non-point sources discharging to surface waters in the Central Valley, California, 1985" prepared by the RWQCB Central Valley Region in 1988.


	1		MERC	CURY	LOADING .	TABLE				
				Me	rcury Loading	(pound	s/year)			
Source	Delta	Note	Sacramento Basin	Note	San Joaquin Basin	Note	Bay Region	Note	Sacramento River above dams	Note
Agricultural	В	1	В	6	В	11		16		
Mine Drainage		2	В	7	В	12	1.00	17	В	21
M&I Wastewater (POTW)	В	3	В	8	В	13	1543	18		
Urban Runoff	В	4	В	9	В	14	330	19	···	
Flow Regulation										
Total Load							1873			
Basin Emission	Α	5	463	10	Α	15	1. 47	20	2500	22

Note: Numerical values listed in italics under the Note column provide the background and references associated with the accompanying load

A - Data available; flow and concentration data available; load calculations required.

B - Further literature review required.

- Source does not contribute significant load of constituent in this watershed.



Mercury Loading Notes

- 1. Further literature review required.
- 2. A report prepared by the Central Valley RWQCB in 1992 and entitled "Inactive mine drainage in the Sacramento Valley" did not estimate mercury loads because sites visited were dry and not discharging wastewater. Mercury loads from the Newton and New Idria Mines were estimated as very small (less than 3 lbs/year) in "A mass loading assessment of major point and non-point sources discharging to surface waters in the Central Valley, California, 1985" prepared by the RWQCB, Central Valley Region in 1988. Although inactive mines could contribute mercury in surface runoff, it is unlikely that represent a significant source.
- 3. See Note 1 for explanation.
- 4. See Note 1 for explanation.
- 5. Mercury concentrations are available from various sampling locations within the Delta and at the San Joaquin River inflow to the Delta. Most of this data can be found at the Interagency Ecological Program web site. Work is in progress to acquire matching discharge data and calculate loads.
- 6. See Note 1 for explanation.
- 7. See Note 1 for explanation.
- 8. See Note 1 for explanation.
- 9. See Note 1 for explanation.
- 10. Total emission in Sacramento River as measured at Freeport. Reported in "Sacramento River Mercury Control Planning Project, Final Project Report" prepared for Sacramento Regional County Sanitation Agency by Larry Walker and Associates, 1997.
- 11. See Note 1 for explanation.
- 12. See Note 2 for explanation.
- 13. See Note 1 for explanation.
- 14. See Note 1 for explanation.
- 15. See Note 5 for explanation.
- 16. Source does not contribute significant load of constituent in this watershed.
- 17. See Note 16 for explanation.

Mercury Loading Notes

- 18. Reported in Table 19 of "State of the Estuary: A report on conditions and problems in San Francisco Bay/Sacramento-San Joaquin Delta Estuary' San Francisco Estuary Project, 1992. Middle of range of values used .
- 19. See Note 18.
- 20. See Note 16 for explanation.
- 21. See Note 1 for explanation.
- 22. Emission was calculated using flow and concentration data for release from Shasta Dam. No similar data was available for Oroville and Nimbus Dams so this is probably an underestimate. Reported in "A mass loading assessment of major point and non-point sources discharging to surface waters in the Central Valley, California, 1985" prepared by the RWQCB Central Valley Region in 1988. The emission is the product of a large flow and a small concentration, probably based on limited data. Consequently, a small error in concentration can greatly effect the emission rate.


			SELENII	UM LC	ADING TABLE	- 1				
			S	eleniun	n Loading (thousan	ds of p	ounds/year)		<u> </u>	
Source	Delta	Note	Lower Sacramento Basin below dams	Note	San Joaquin Basin	Note	Bay Region	Note	Upper Sacramento Basin above Dams	Note
Agricultural	Α	1	Α	6	Α	11		16	Sept.	
Mine Drainage		2	整合公司会区域。	7		12	Set Wester (T)	17		
M&I Wastewater (POTW)		3		8		13	7	18		
Urban Runoff	12 July 10 10 10 10 10 10 10 10 10 10 10 10 10	4	क्षेत्रमेष्ट्रयाच्या करही हर ५००	9	Barrier of the confirment	14	på, Satsap Mari	19	da ee ,	
Flow Regulation	t mit on		Bartin many that the first of		September 1		SQ Prod Kyar		851° 61	
Total Load							7			
Basin Emission	В	5	2	10	9	15	В	20	В	21

Note: Numerical values listed in italics under the Note column provide the background and references associated with the accompanying load

A - Data available; flow and concentration data available; load calculations required.


B - Further literature review required.

- Source does not contribute significant load of constituent in this watershed.



	SELENIUM TABLE - 2	
Sel	enium in the San Joaquin River Tributaries	3
Tributary	Dissolved Selenium Loads in Tributaries as % of those in San Joaquin River at Vernalis	Note
Stanislaus River	2	1
Toulumne River	3	1
Salt/Mud Sloughs	71	1
Merced River	2	1
San Joaquin above Salt Slough Confluence	3	1

Note 1: Values obtained from the U.S. Geological Survey Water Resources Investigation Report 88-4186



Selenium Loading Notes

- 1. Data available; flow and concentration data available; load calculations required.
- 2. None of the references on mine drainage reviewed by the consultant team indicated that selenium was a significant constituent of mine drainage waters.
- 3. Selenium is not usually detected in municipal wastewaters or most industrial wastewaters but it is found in oil refinery wastewater. Municipal and industrial wastewaters are probably an insignificant source in the Delta. See Note 18 for more information.
- 4. Most urban runoff sampling studies have not included selenium. Selenium was not measured in the 1980s in EPA's National Urban Runoff Program (NURP). Selenium data was included in the most recent urban runoff monitoring in Sacramento as reported in "Sacramento NPDES Stormwater Discharge Characterization Program, 1996 Update Report" prepared for the city of Sacramento by Larry Walker and Associates. Some selenium concentration measurements were made in the cities of Eugene and Portland in the early 1990s. Selenium was not detected in any Eugene samples. A few measurements of 0.001 and 0.002 mg/l were recorded in Portland with a detection limit 0.001 mg/l. The data indicates that selenium is not present in urban runoff in high concentrations and is probably not significant compared to emissions from oil refineries and certain agricultural areas. In order to obtain a more precise estimate of selenium in urban runoff, additional monitoring is needed using a low detection limit.
- 5. Further literature review required.
- 6. See Note 1 for explanation.
- 7. See Note 2 for explanation.
- 8. Selenium is not usually detected in municipal wastewaters or most industrial wastewaters but it is found in oil refinery wastewater. Municipal and industrial wastewaters are probably an insignificant source in the Sacramento Basin. See Note 18 for more information.
- 9. See Note 4 for explanation.
- 10. Reported in Table 19 of "State of the Estuary: A report on conditions and problems in San Francisco Bay/Sacramento-San Joaquin Delta Estuary" San Francisco Estuary Project, 1992.
- 11. See Note 1 for explanation.
- 12. See Note 2 for explanation.
- 13. Selenium is not usually detected in municipal wastewaters or most industrial wastewaters but it is found in oil refinery wastewater. Municipal and industrial wastewaters are probably an insignificant source in the San Joaquin Basin. See Note 18 for more information.


Selenium Loading Notes

- 14. See Note 4 for explanation.
- 15. Selenium load in the San Joaquin River at Vernalis is reported as 4.6 tons/year in U. S. Geological Survey Water-Resources Investigations Report 88-4186. The same value for input to San Francisco Bay from the delta is reported in Table 19 of "State of the Estuary: A report on conditions and problems in San Francisco Bay/Sacramento-San Joaquin Delta Estuary" San Francisco Estuary Project, 1992.
- 16. Agricultural drainage is an insignificant source of wastewater in the Bay Area.
- 17. See Note 2 for explanation.
- 18. Selenium loads to San Francisco Bay are reported in "Mass Emissions Reduction Strategy for Selenium" prepared by San Francisco Bay RWQCB in 1992. The loads are estimated as 7.1 kg/day from oil refineries, 2.2 kg/day from municipal wastewater treatment plants and 2 kg/day from riverine sources under average flow conditions. No selenium was detected in samples of municipal wastewater. The RWQCB assumed that it was present in municipal wastewater at the detection limit used in the analyses and thus calculated 2.2 kg/day. The RWQCB noted this was a probable overstatement. It is worth noting that the estimated load to the bay from riverine sources (1,600 lbs/yr) is much lower than the sum of the Sacramento and San Joaquin River inputs to the Bay-Delta system (11,000 lbs/yr reported in "State of the Estuary: A report on conditions and problems in San Francisco Bay/Sacramento-San Joaquin Delta Estuary" San Francisco Estuary Project, 1992. Perhaps, this is attributable chemical reactions and biological uptake in the Delta.
- 19. See Note 4 for explanation.
- 20. See Note 5 for explanation.
- 21. See Note 5 for explanation.

		CHLOF	RPYRIFOS LOADING	TABLE		
			Chlorpyrifos Loading (oounds/ye	ar)	
Source	Delta	Note	Sacramento Basin	Note	San Joaquin Basin	Note
Agricultural	В	1	A	4	А	7
Urban Runoff Total Load	Α	2	A	5	Α	8
Basin Emission	В	3	В	6	В	9

Note: Numerical values listed in italics under the Note column provide the background and references associated with the accompanying load A - Data available; flow and concentration data available; load calculations required.

⁻ Source does not contribute significant load of constituent in this watershed.



B - Further literature review required.

Chlorpyrifos Loading Notes

General Notes


- Applied to almond orchards in January and February and again in May through August.
- Applied to alfalfa fields in March.
- Particle bound compound.
- 1. Further literature review required.
- 2. One study (Conner, 1996) reports chlorpyrifos concentrations in urban runoff from the cities of Stockton and Sacramento and the San Francisco Bay Area. The concentration from the City of Stockton could be used to calculate a load for the Delta. However, further investigation is required to determine if discharge data can be matched to the sampling events and locations.
- 3. See Note 1 for explanation.
- 4. Chlorpyrifos concentration data is reported for the Sacramento River at Sacramento in USGS Open File Report 95-110. The sampling frequency was monthly for the period 1991-1994. Discharge data for the Sacramento River is available. Load calculations are in progress.
- 5. See Note 2 for explanation.
- 6. See Note 1 for explanation.
- 7. Several studies report chlorpyrifos concentration in the San Joaquin river at various locations (USGS, 1995, Open File Report 95-165); (USGS, 1995, Open File Report 95-110); (Foe, Detection of Pesticides in the San Joaquin Basin); (Department of Pesticide Regulation, 1991-1993, San Joaquin River Study). Further investigation is required to determine if discharge data can be matched to the sampling events and locations.
- 8. See Note 1 for explanation.
- 9. See Note 1 for explanation.

	·	DIAZ	ZINON LOADING TA	BLE		
			Diazinon Loading (pou	ınds/year)		
Source	Delta	Note	Sacramento Basin	Note	San Joaquin Basin	Note
Agricultural	В	1	319	4	116	7
Urban Runoff	Α	2	A	5	В	8
Total Load			319		116	
Basin Emission	В	3	В	6	В	9

Note: Numerical values listed in italics under the Note column provide the background and references associated with the accompanying load A - Data available; flow and concentration data available; load calculations required.

B - Further literature review required.

- Source does not contribute significant load of constituent in this watershed.



Diazinon Loading Notes


General Notes

- Applied to almond orchards in January and February and again in May through August.
- Applied to alfalfa fields in March.
- 1. Further literature review required.
- 2. One study (Conner, 1996) reports diazinon concentrations in urban runoff from the cities of Stockton and Sacramento and the San Francisco Bay Area. The concentration from the City of Stockton could be used to calculate a load for the Delta. However, further investigation is required to determine if discharge data can be matched to the sampling events and locations.
- 3. See Note 1 for explanation.
- 4. Loads were estimated based on measured diazinon concentrations and measured streamflows. Diazinon concentrations in the San Joaquin River at Vernalis were obtained from The USGS WATSTOR database and the USGS Open File Report 95-110. Diazinon data in the Sacramento River at Sacramento were obtained from the USGS Open File Report 95-110. Flows in the Sacramento River are from the USGS gage at Freeport (#11447650). Flows in the San Joaquin River are from the USGS gage at Vernalis (#11303500). At Vernalis loads were estimated for years 1991, 1993, and 1994. The average is reported in the table. At Sacramento loads were estimated for 1993 and 1994 and the average reported. Note, the estimated diazinon load at Sacramento includes urban runoff from Sacramento and surrounding areas in addition to agricultural runoff. Non-detect data was not included in the loads analysis.
- 5. See Note 2 for explanation.
- 6. See Note 1 for explanation.
- 7. See Note 4 for explanation.
- 8. See Note 1 for explanation.
- 9. See Note 1 for explanation.

	CARBOFURAN LOADING	TABLE	
	Carbofuran (oounds/year)	
Source	Sacramento Basin	Note	
Agricultural	A	1	
Total Load			
Basin Emission	A	2	

Total Load

Note: Numerical values listed in italics under the Note column provide the background and references associated with the accompanying load A - Data available; flow and concentration data available; load calculations required.



Carbofuran Loading Notes


General Notes

- Applied to alfalfa fields in March and to rice fields from April through June.
- 1. Several studies report carbofuran concentrations detected in the Sacramento River at various locations (USGS, 1995, Open File Report 95-110); (Crepeau et. al.); (Department of Fish and Game, Rice Pesticide Concentrations in the Sacramento River and Associated Agricultural Drains); (Department of Water Resources, August 1989). Discharge data is available for many of the locations where carbofuran was sampled. Load calculations are in progress.
- 2. See Note 1 for explanation.

			NITRATE	LOADI	NG TABLE			
			Nitrate	Loading	(thousands of pou	nds/yea	r)	
Source	Delta	Note	Bay Region	Note	Sacramento Basin	Note	Sacramento River above Dams	Note
Agricultural	A	1		6	В	11	В	16
Urban Runoff	77	2	166	7	1790	12	Balancia de la Cara	17
Flow Regulation	В	3	В	8	В	13	В	18
Construction	В	4	В	9	В	14	В	19
Total Load	77				1790			
Basin Emission	В	5	В	10	В	15	В	20

Note: Numerical values listed in italics under the Note column provide the background and references associated with the accompanying

- A Data available; flow and concentration data available; load calculations required.
- B Further literature review required.
 - Source does not contribute significant load of constituent in this watershed.



Nitrate Loading Notes

- 1. Nitrate concentrations are available from various sampling locations within the Delta and at the San Joaquin River inflow to the Delta. Most of this data can be found at the Interagency Ecological Program web site. Work is in progress to acquire matching discharge data and calculate loads.
- 2. Nitrate loads were calculated by Woodward-Clyde for the Contra Costa Clean Water Program (Contra Costa Clean Water Program, 1994). The loads assessment model is based upon a relationship between rainfall quantities, runoff pollutant concentrations, and the relationship between pollutant loads and land use. The loads assessment model contains the following assumptions:
 - Uniform precipitation between isohyets
 - Constant runoff coefficient based upon land use
 - Runoff water quality was constant for each land use
 - Isohyetals based on average annual precipitation

The reported load in the loading table is from Figure 4-1 of the report (Contra Costa Clean Water Program, 1994).

- 3. Further literature review required.
- 4. See Note 3 for explanation.
- 5. See Note 3 for explanation.
- 6. Source does not contribute significant load of constituent in this watershed.
- 7. See Note 2 for explanation.
- 8. See Note 3 for explanation.
- 9. See Note 3 for explanation.
- 10. See Note 3 for explanation.
- 11. See Note 3 for explanation.
- 12. Nitrate loads were calculated for the Sacramento NPDES Stormwater Discharge Characterization Program (Larry Walker & Associates). Loads were initially calculated in 1992 using the following methodology:
 - Regression models were developed showing the relationship of urban runoff pollutant discharge factors.

Nitrate Loading Notes

- The regression equations were then used as input to a continuous simulation model for Sacramento urban runoff mass loading over a 58 year period.
- The model was refined in 1996, using the updated database of urban runoff monitoring data available form the Sacramento NPDES Stormwater Monitoring Program. the load reported in the loading table is from Table 15 of the report (Larry Walker & Associates).
- 13. See Note 3 for explanation.
- 14. See Note 3 for explanation.
- 15. See Note 3 for explanation.
- 16. See Note 3 for explanation.
- 17. See Note 6 for explanation.
- 18. See Note 3 for explanation.
- 19. See Note 3 for explanation.
- 20. See Note 3 for explanation.

REFERENCES

- Association of Bay Area Governments, 1992. San Francisco Estuary Project State of the Estuary: A Report on Conditions and Problems in the San Francisco Bay/Sacramento-San Joaquin Delta Estuary. June (Table 19, pp. 172) Note: Data from Table 19 was adapted from Davis et al., 1991.
- Contra Costa Clean Water Program, FY 1994-95. Monitoring Report.
- California Urban Water Agencies. April 1995. Study of Drinking Water Quality in Delta Tributaries.
- Central Valley Regional Water Quality Control Board. December 1995. Insecticide Concentrations and Invertebrate Bioassay Mortality in Agriculture Return Water.
- Central Valley Regional Water Quality. March 1989. Mass Loading Assessment of Major Point and Non Point Sources Discharging to Surface Waters in Sacramento Valley, CA. Draft Staff Report.
- Christopher Foe. Detection of Pesticides in San Joaquin Basin. Central Valley Regional Water Quality Control Board memos 1989-1990.
- City of Modesto. May 1993. Part 2 NPDES Storm Water Permit Application.
- Contra Costa Clean Water Program, FY 1994-95. Monitoring Report
- Contra Costa Clean Water Program, 1994. Contra Costa Clean Water Program Loads Assessment Report.
- Crepeau, Kathryn, Kuivila, Kathryn and Domagalski, Joseph, 1990-1992. Concentrations of Dissolved Rice Pesticides in the Colusa Basin Drain and Sacramento River, California.
- CRWQCB, Central Valley Region, July 1992. Inactive Mine Drainage in the Sacramento Valley, California..
- Department of Fish and Game. Rice Pesticide Concentrations in Sacramento River and Associated Agricultural Drains. Carbofuran monitored from 1987 through 1985.
- Department of Pesticide Regulation. San Joaquin River Study. 1991-1993.
- Department of Water Resources. August 1989. The Delta as A Source of Drinking Water: Monitoring Results 1983-1987.

X:\CALFED\REFS.DOC

REFERENCES

- EPA. 1992. San Francisco Estuary Project State of the Estuary: A Report on Conditions and Problems in the San Francisco Bay/Sacramento-San Joaquin Delta Estuary. (Table 19, pp. 172)
- Fresno-Clovis Storm Water Quality Management Program. April 1995. Estimate of Annual Pollutant Loads to Waters of the United States.
- James Scanlin. 1997. Characterization of Insecticide Use and Presence in the Castro Valley Creek Watershed. Draft Report Alameda County Flood Control and Water Conservation District.
- Larry Walker & Associates. Sacramento NPDES Stormwater Discharge Characterization Program. 1996 DCP Update Report.
- Sacramento Regional Sanitation District. March 1997. Sacramento River Mercury Control Project.
- San Francisco Estuary Institute. Regional Monitoring Program for Trace Substances: 1995 Annual Report.
- San Francisco Estuary Institute. Regional Monitoring Program for Trace Substances: 1995 Annual Report.
- Taylor, K., Pease, W., Lacy, J., Carlin, M. 1992. Mass Emissions Reduction Strategy for Selenium.
- USGS. 1993. Diazinon Concentrations in the Sacramento and San Joaquin Rivers and San Francisco Bays, California, February 1993. Open File Report 93-440.
- USGS. 1995. Dissolved Pesticide Data for San Joaquin River at Vernalis and the Sacramento River at Sacramento, California, 1991-1994. Open -File Report 95-110.
- USGS. 1995. Nonpoint Sources of Pesticides in the San Joaquin River, California: Input From Winter Storms, 1992-1993. Open File Report 95-165.
- USGS. 1988. Preliminary Assessment of Sources, Distribution, and Mobility of Selenium in the San Joaquin Valley, California.
- Valerie Connor. January 1996. Chlorpyrifos in Urban Storm Runoff. Memorandum to Jerry Bruns Central Valley Regional Water Quality Control Board.

X:\CALFED\REFS.DOC

DESILITS INTERNET SEARCH			
WATER QUALITY DATA			
RESOURCE/AGENCY/DEPARTMENT	ADDRESS	RELEVANT	REVIEW RESULTS
		SUBJECTS/CATEGORIES	
Department of Water Resources/Division of Flood Management	http://cdcc.watcr.ca.gov	Current & Historical Data	Retrieved daily data for April for Freeport station, no monthly data available,
		Single & Group Stations	Error messages for historical data
Interagency Ecological Program	http://www.icp.ca.gov	IEP Long Term Monitoring Data	Retrieved Discrete Sampling Data for Metals, Pesticides and Water Quality &
		Discrete Water Quality Sampling	DAYFLOW data for 1984 - 1995
		DAYFLOW (estimates of net freshwater flow)	
USGS/Water Resources of California	http://water.wr.usgs.gov/	Pesticides in the Hydrologic System-National Assessment	Retrieved Summaries from NAWQA Pesticide Studies & Bibliography
		Sacramento River Basin/USGS National Water Quality Assessment	Retrieved NAWQA Study Areas, no access to Sacramento River Basin study
		Pesticide Links	No significant results from following pesticide links
California Department of Water Resources	http://wwwdwr.water.ca.gov/	Water Conditions	Retrieved Summary Report for Apr. 16 with flow data for various stations
		California Water Conditions	No relevant information from CA Water Info page
		State Water Project	Link to Operations Control Office Home Page, see below
State Water Project/Operations Control Office	http://www.oco.water.cagov/	SWP Operational Reports	Retrieved monthly summary of water operations- flows for the month- for March 97
		Buy Delta Standards	Winter-Run and Delta Smelt ESA biological opinions
		Delta Hydrology and Quality Conditions	Retrieved data for the past 30 days
		Delta Environmental Compliance Reports	No access possible
State Water Resources Control Board	http://www.swrcb.ca.gov/	Plans, Policies, Staff Reports, Publications	Retrieved list of staff reports and publications
		Links to other sites	No significant results
California Environmental Resources Evaluation System	http://ceres.ca.gov/	Web Scarch by geographic area, theme, data type	Did a search with no significant results
	150 160 200	Date Mariania	Only Jestifian of manifestine program no data
Bay Delia and Special Projects Division	Green Green	6	M. X.
CALFED/Bay-Delia Program	http://calfed.ca.gov/	Phase I Final Report, Current Phase II Alternative	No relevant information
California Rivers Assessment (CARA)	http://cndcavor.dcs.ucdavis.cdu/cara	Information by River Basin	Retrieved information for Sacramento Basin, only maps, no data